



# Combination Water Slide Model 1868

## Specifications

**Description:** Double flume fiberglass and 30" I.D. polyethylene combination slide, each featuring one and ¾ turns.

**Centerline Run:** Fiberglass (open) 141' 6"; Poly (closed) 112' 10"

**Entry Height:** 19' 3"

**Platform Size:** 8' x 8'

**Deck Space Requirement:** 50' 9" x 35' 8" \*

## Features

- 36" inside diameter fiberglass open flume.
- 30" inside diameter polyethylene closed flume.
- Fiberglass Flume: ultra violet stabilized gelcoat.
- Polyethylene Flume: color impregnated UV stabilized.
- Platform: Aqua-Plast coated textured aluminum surface.
- Stairs: 7" rise, 11" tread, 36" wide; Aqua-Plast coated textured aluminum surface; closed risers.
- Stainless steel base plates, hardware and anchor bolts.
- Designed with flexibility to allow for sloping pool decks.
- Water flow required: Open: 600-800 gpm; Closed: 50 gpm recommended; 30 to 60 gpm required.
- Splash down dimension: 25' x 20'
- Minimum water depth: 3'
- USA Made

## Options

- Deluxe Series: Stainless steel polyester powder coated except tower and flume posts which are mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- Hot dipped galvanized available.
- Stairs: (a) 48" width; (b) Inner handrails (if applicable); (c) Spiral stairs.
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric; (d) Tongue & groove decking with the wood or steel roofs.
- Water pumps & covers
- Perimeter Fencing
- Factory installation or on-site technical assistance.



PO Box 270, Baker City, OR 97814  
 (541) 523-0224 (800) 252-8475 Fax (541) 523-0231  
 www.naturalstructures.com - info@naturalstructures.com

Note: Closed risers now standard for all stairs.

\*Space requirements may vary with options chosen.