



Hillside Slide Model: Dolhare

Specifications

Description: Single polyethylene flume designed for hillside & landscape applications.
Slide Run: 74' 2"

Elevation Height: 23' 8"
Height Above Water Level: 2'
Space Requirements: 53' x 23' 7"

Features

- 30" inside diameter polyethylene flume.
- Polyethylene Flume: color impregnated UV stabilized.
- Stairs & Deck: available.
- Multiple stair locations & configurations.
- Stairs & Platform: determined by the slope.
- Stainless steel base plates, hardware and anchor bolts.
- Designed with flexibility to allow for sloping pool decks.
- 14-20 gpm water flow recommended; 8 to 40 gpm required.
- Splash down dimension 13' x 20'
- Minimum water depth: 5' 6"
- USA Made

Options

- Deluxe Series: Complete package is stainless steel polyester powder coated except the stair treads and deck which are vinyl coated mild steel.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating with polyester powder coat topcoat.
- Hot dipped galvanized.
- Stairs: a) 7" rise, 11" tread, 36" wide; textured aluminum; closed risers (b) 48" width; (c) Inner handrails (if applicable)
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: Polyethylene plastic roof.
- Factory installation or on-site technical assistance.
- Water pumps & covers



PO Box 270, Baker City, OR 97814
(541) 523-0224 (800) 252-8475 Fax (541) 523-0231
www.naturalstructures.com - info@naturalstructures.com

*Space requirements may vary with options chosen.