



Pool Slide Model 9106

Specifications

Description: Single 30" I.D. flume slide, with a 90° curve.

Slide Run: 23'

Platform Height: 5' 11"

Platform Size: 4' x 4'

Space Requirements: 17' x 18' 2"*

Features

- 30" inside diameter polyethylene flume.
- Flume: color impregnated UV stabilized.
- Deck: vinyl coated.
- Stairs: 8" rise, 8" tread, 24" wide; vinyl coated.
- Multiple stair locations & configurations.
- Stainless steel base plates, hardware and anchor bolts.
- Designed with flexibility to allow for sloping pool decks.
- 14-20 gpm water flow recommended; 8 to 40 gpm required.
- Splash down dimension 12' 6" x 20'
- Minimum water depth: 2'
- USA Made

Options

- Deluxe Series: Complete package is stainless steel polyester powder coated except the stairs and deck which are vinyl coated mild steel.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating with polyester powder coat topcoat.
- Hot dipped galvanized.
- Stairs: (a) 7" rise, 11" tread, 36" wide; textured aluminum; closed risers; (b) Inner handrails (if applicable).
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: Polyethylene plastic roof.
- Factory installation or on-site technical assistance.
- Water pumps & covers



PO Box 270, Baker City, OR 97814

(541) 523-0224 (800) 252-8475 Fax (541) 523-0231

www.naturalstructures.com - info@naturalstructures.com