



## Pool Slide Model 9308

### Specifications

**Description:** Double 30" I.D. flume slide, (2) 90° curves.

**Slide Run:** 21' 6"

**Platform Height:** 7' 11"

**Platform Size:** 4' x 4'

**Space Requirements:** 31' 10" x 12' 2" \*

### Features

- 30" inside diameter polyethylene flumes.
- Flume: color impregnated UV stabilized.
- Deck: vinyl coated.
- Stairs: 8" rise, 8" tread, 24" wide; vinyl coated.
- Multiple stair locations & configurations.
- Stainless steel base plates, hardware and anchor bolts.
- Designed with flexibility to allow for sloping pool decks.
- 14-20 gpm water flow (each flume) recommended; 8 to 40 gpm required.
- Splash down dimension 41' 10" x 20'
- Minimum water depth: 5' 6"
- USA Made



### Options

- Deluxe Series: Complete package is stainless steel polyester powder coated except the stairs and deck which are vinyl coated mild steel.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating with polyester powder coat topcoat.
- Hot dipped galvanized.
- Stairs: (a) 7" rise, 11" tread, 36" wide; textured aluminum; closed risers; (b) Inner handrails (if applicable).
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: Polyethylene plastic roof.
- Factory installation or on-site technical assistance.
- Water pumps & covers

PO Box 270, Baker City, OR 97814  
(541) 523-0224 (800) 252-8475 Fax (541) 523-0231  
[www.naturalstructures.com](http://www.naturalstructures.com) - [info@naturalstructures.com](mailto:info@naturalstructures.com)

\*Space requirements may vary with options chosen.