



## Fiberglass Water Slide Model 1845

### Specifications

**Description:** Single open flume fiberglass slide (3) 270° reverse curves.

**Slide Run:** 165' 10"

**Platform Height:** 20' 5"

**Platform Size:** 8' x 8'

**Space Requirements:** 22' x 44' 1"

### Features

- 36" inside diameter fiberglass flumes.
- Flume: Ultra Violet stabilized Gelcoat.
- Platform: textured aluminum.
- Stairs: 7" rise, 11" tread, 36" wide; textured aluminum; closed risers.
- Stainless steel base plates, hardware and anchor bolts.
- Designed with flexibility to allow for sloping pool decks.
- 800 gpm water flow required.
- Splash down dimension 13' x 20'
- Minimum water depth: 3'
- USA Made

### Options

- Deluxe Series: Stainless steel polyester powder coated except the tower posts and stair channels, which are mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat.
- Hot dipped galvanized available.
- Stairs: (a) 48" width; (b) Inner handrails (if applicable); (c) Spiral stairs.
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric; (d) Tongue & groove decking with the wood or steel roofs.
- Water pumps & covers
- Perimeter Fencing
- Factory installation or on-site technical assistance.



PO Box 270, Baker City, OR 97814  
 (541) 523-0224 (800) 252-8475 Fax (541) 523-0231  
 www.naturalstructures.com - info@naturalstructures.com

\*Space requirements may vary with options chosen.