



## Water Slide Model 1617

### Specifications

**Description:** Single 30" I.D. flume slide in a figure 8.

**Slide Run:** 104' 5"

### Features

- 30" inside diameter polyethylene flume
- Flume: color impregnated UV stabilized
- Platform: textured aluminum
- Stairs: 7" rise, 11" tread, 36" wide; textured aluminum; closed risers
- Stainless steel base plates, hardware and anchor bolts
- Designed with flexibility to allow for sloping pool decks
- 20 gpm water flow recommended; 20 to 40 gpm required.
- Splash down dimension 13' x 20'
- Minimum water depth: 3'
- USA Made



PO Box 270, Baker City, OR 97814  
(541) 523-0224 (800) 252-8475 Fax (541) 523-0231  
[www.naturalstructures.com](http://www.naturalstructures.com) - [info@naturalstructures.com](mailto:info@naturalstructures.com)

**Platform Height:** 16' 9"

**Platform Size:** 6' x 6'

**Space Requirements:** 17' 5" x 32' 7" \*

### Options

- Deluxe Series: stainless steel polyester powder coated except the tower posts and stair channels, which are mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat.
- Hot dipped galvanized available
- Stairs: (a) 48" width; (b) Inner handrails (if applicable); (c) Spiral stairs.
- Stair Configurations: Many variations available
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric; (d) Tongue & groove decking with the wood or steel roofs.
- Water pumps & covers
- Perimeter Fencing
- Factory installation or on-site technical assistance.

\*Space requirements may vary with options chosen.