



Hillside Slides Models 1682 and 1686

Specifications

Description: Polyethylene flume body slides with fiberglass exit lanes
Centerline Run: 45' 4" (1682) & 93' 9" (1686)

Entry Height: 11' 0" (1682) & 16' 6" (1686)
Platform Size: *Platform and stairs done by others.
Space Requirements: 52' 3" x 57' 10"

Features

- 30" inside diameter polyethylene flumes.
- Flume: color impregnated UV stabilized.
- Stairs & Platform: available.
- Stainless steel base plates, hardware and anchor bolts.
- Flume posts are required in accordance to the elevation.
- Fiberglass exit lanes.
- 20 to 40 gpm water flow (each flume) required
- Self-enclosed recirculating system (no pool required)
- USA Made.

Model 1682: Yellow Flume
 Model 1686: Blue Flume

Options

- Deluxe Series: Stainless steel polyester powder coated except tower and flume posts which are mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- Hot dipped galvanized available.
- Stairs: (a) 48" width; (b) Inner handrails (if applicable); (c) Spiral stairs.
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric; (d) Tongue & groove decking with wood or steel roofs.
- Water pumps & covers
- Perimeter Fencing
- Factory installation or on-site technical assistance.



PO Box 270, Baker City, OR 97814
 (541) 523-0224 (800) 252-8475 Fax (541) 523-0231
 www.naturalstructures.com - info@naturalstructures.com

*Space requirements may vary with options chosen.