

Landscape Slide Model: DeRocker

Specifications

Description: 30" I.D. Single polyethylene flume slide featuring 360° and 90° curves **Centerline Run**: 68' 11"

Features

- 30" Inside diameter polyethylene flume.
- Polyethylene Flume: Color impregnated UV stabilized.
- Stairs & Platform: Available.
- Water flow required: 20-40 gpm.
- Splash down dimension: 12' 6" x 20' 0"
- Minimum water depth: 5' 6"
- USA Made



Matural

(541) 523-0224 (800) 252-8475 Fax (541) 523-0231 www.naturalstructures.com - info@naturalstructures.com

Entry Height: 14' 0"

Platform Size: *Platform and stairs done by others. Space Requirements: 11' 10" x 31' 0" *

Options

- Deluxe Series: Stainless steel polyester powder coated except tower and flume posts which are mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- Hot dipped galvanized available.
- Stairs: Aqua-Plast coated textured aluminum surface; closed risers (a) 7" rise, 11" tread, 36" wide
 (b) 48" width; (c) Inner handrails (if applicable)
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric;
 (d) Tongue & groove decking with wood or steel roofs.
- Water pumps & covers
 Derimeter Conging
- Perimeter Fencing
- Factory installation or on-site technical assistance.

*Space requirements may vary with options chosen.