



Pool Slide Model 0085

Note: Closed risers now standard for all stairs.
Vertical slats now standard on all stair handrails.

Specifications

Description: Double flume slide, one 30" I.D. flume and one 24" O.D. flume.

Centerline Run: 21' 0" & 16' 7"

Entry Height: 7' 0"

Platform Size: 4' x 4'

Space Requirements: 17' 0" x 17' 2"*

Options Shown: Polyethylene plastic Tower Roof

Features

- 30" inside & 24" outside diameter polyethylene flumes.
- Deck: Aqua-Plast coated textured aluminum surface.
- Stairs: 8" rise, 8" tread, 24" wide; Aqua-Plast coated textured aluminum surface.
- Multiple stair locations & configurations.
- Stainless steel base plates, hardware and anchor bolts.
- Designed with flexibility to allow for sloping pool decks.
- 14-20 gpm water flow (each flume) recommended; 8 to 40 gpm required.
- Splash down dimension 22' 4" x 20'
- Minimum water depth: 3' 6"
- USA Made

Options

- Deluxe Series: Complete package is stainless steel polyester powder coated except the stair treads and deck which are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating with polyester powder coat topcoat, except stair treads and deck which are textured Aqua-Plast coated aluminum.
- Stairs: (a) 7" rise, 11" tread, 36" wide; textured aluminum; closed risers; (b) Inner handrails (if applicable).
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: Polyethylene plastic roof.
- Factory installation or on-site technical assistance.
- Water pumps & covers



PO Box 270, Baker City, OR 97814 (541) 523-0224 (800) 252-8475 www.naturalstructures.com - info@naturalstructures.com

*Space requirements may vary with options chosen.