



Closed Fiberglass Drop Slide Model 5021

Specifications

Description: Single 32" I.D. closed flume fiberglass drop slide pool slide.

Centerline Run: 11' 10"

Entry Height: 8' 7"

Platform Size: N/A

Space Requirements: 4' 9" x 11' 4" *

Note: Deep End Required

Features

- 32" inside diameter fiberglass flume.
- Flume: ultra violet stabilized gelcoat.
- Platform & Stairs: by others.
- Stainless steel base plates, hardware and anchor bolts.
- Designed with flexibility to allow for sloping pool decks.
- 20-40 gpm water flow required.
- Splash down dimension: 13' x 20'
- Minimum water depth: 12'
- USA Made

Options

- Deluxe Series: Stainless steel polyester powder coated except tower and flume posts which are mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- Hot dipped galvanized available.
- Stairs: (a) 36" width; (b) Inner handrails (if applicable); (c) Spiral stairs.
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric; (d) Tongue & groove decking with the wood or steel roofs.
- Water pumps & covers
- Perimeter Fencing
- Factory installation or on-site technical assistance.



PO Box 270, Baker City, OR 97814
 (541) 523-0224 (800) 252-8475 Fax (541) 523-0231
 www.naturalstructures.com - info@naturalstructures.com

*Space requirements may vary with options chosen.