



## Water Slide Model 1636\*\*

\*\*Can be ordered as Phase 1 of Water Slide Model 1641 or Water Slide Model 1884.

### Specifications

**Description:** Single 30" I.D. flume slide with three turns in a cloverleaf.

**Centerline Run:** 145' 0"

**Entry Height:** 24' 5"

**Platform Size:** 8' x 8'

**Space Requirements:** 38' 4" x 34' 7" \*

### Features

- 30" inside diameter polyethylene flume
- Flume: color impregnated UV stabilized
- Platform: Aqua-Plast coated textured aluminum surface.
- Stairs: 7" rise, 11" tread, 36" wide; Aqua-Plast coated textured aluminum surface; closed risers.
- Stainless steel base plates, hardware and anchor bolts
- Designed with flexibility to allow for sloping pool decks
- 50 gpm water flow recommended; 30 to 60 gpm required
- Splash down dimension 12' 6" x 20'
- Minimum water depth: 3'
- USA Made

### Options

- Deluxe Series: Stainless steel polyester powder coated except tower and flume posts which are mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- Hot dipped galvanized available
- Stairs: (a) 48" width; (b) Inner handrails (if applicable); (c) Spiral stairs
- Stair Configurations: Many variations available
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric; (d) Tongue & groove decking with the wood or steel roofs.
- Water pumps & covers
- Perimeter Fencing
- Factory installation or on-site technical assistance.



PO Box 270, Baker City, OR 97814  
 (541) 523-0224 (800) 252-8475 Fax (541) 523-0231  
[www.naturalstructures.com](http://www.naturalstructures.com) - [info@naturalstructures.com](mailto:info@naturalstructures.com)

Note: Closed risers now standard for all stairs.

\*Space requirements may vary with options chosen.